

# EW2000V

	PERFORMAMCE DATA	COOLING		HEATING	
	NUMBER OF ROWS	4 ROWS	6 ROWS	2 ROWS	
				HEATING BY CHILLER	HEATING SYSTEM
	CAPACITY IN Kbtu/h / kW	52.2 / 15.4	65.9 / 19.3	42	90.2
	SESIBLE CAPACITY IN Kbtu/h / kW	43.9	51.3		
	WATER FLOW IN GPM	10.6	13.2	8.9	9.3
	WATER PRESSURE DROP IN FT H <sup>2</sup> O	7.7	7.2	9.7	9.9
	NOISE LEVEL (dBA)	42.5			
	WEIGHT (kg)	85	89		
CONDITIONS	DRY / WET BULB TEMP.	80°F/67°F - 26.6°C/19.4°C		70°F - 21.1°C	
	WATER TEMP. INLET (°F / °C)	45 / 7		113 / 45	160 / 71
	WATER TEMP. OUTLET (°F / °C)	55 / 12.8		103 / 40	140 / 60
COIL	FACE AREA (ft <sup>2</sup> / m <sup>2</sup> )	4.51 / 0.42			
	LENGTH (MM)	1180			
	AIR FLOW VELOCITY (fpm / m/sec)	443 / 2.3			
	HEADER DIAMETER (in)	1.3/8"			
BLOWER	AIR FLOW (CFM / m <sup>3</sup> / h)	2000 / 3400			
	TYPE	2X DD 9x9			
	MOTOR POWER (HP / kW)	2X 1/3		2X 0.25	
	NO. OF SPEEDS	5			
	HIGH SPEED (RPM)	920			
	POWER SUPPLY	230v/50Hz/1PH			
OPTIONAL	VALVE	ON/OFF / PROP			
	ELECTRIC HEATING (kW)	kW			
	OUTDOOR CONDITIONS	YES / NO			

Noise level at 1.5m distance from ducted (supply and return) unit

D	H	L	A	C	E	B	J	K	M	N
43	100	139	30.5	30.2	26.5	30	0	7/8"	0	0

