

EW450V

	PERFORMAMCE DATA	COOLING		HEATING	
	NUMBER OF ROWS	4 ROWS	6 ROWS	2 ROWS	
				HEATING BY CHILLER	HEATING SYSTEM
	CAPACITY IN Kbtu/h / kW	12.9 / 3.8	15.9 / 4.7	11.3	24.3
	SESIBLE CAPACITY IN Kbtu/h / kW	10.8	11.9		
	WATER FLOW IN GPM	2.6	3.1	2.3	2.5
	WATER PRESSURE DROP IN FT H ² O	4.9	9.8	7.2	7.9
	NOISE LEVEL (dBA)	37.5			
	WEIGHT (kg)	33	34		
CONDITIONS	DRY / WET BULB TEMP.	80°F/67°F - 26.6°C/19.4°C		70°F - 21.1°C	
	WATER TEMP. INLET (°F / °C)	45 / 7		113 / 45	160 / 71
	WATER TEMP. OUTLET (°F / °C)	55 / 12.8		103 / 40	140 / 60
COIL	FACE AREA (ft ² / m ²)	1.2 / 0.11			
	LENGTH (MM)	400			
	AIR FLOW VELOCITY (fpm / m/sec)	375 / 1.9			
	HEADER DIAMETER (in)	7/8"			
BLOWER	AIR FLOW (CFM / m ³ / h)	450 / 765			
	TYPE	DD 7x10			
	MOTOR POWER (HP / kW)	1/8		0.09	
	NO. OF SPEEDS	4			
	HIGH SPEED (RPM)	1400			
	POWER SUPPLY	230v/50Hz/1PH			
OPTIONAL	VALVE	ON/OFF / PROP			
	ELECTRIC HEATING (kW)	kW			
	OUTDOOR CONDITIONS	YES / NO			

Noise level at 1.5m distance from ducted (supply and return) unit

D	H	L	A	C	E	B	J	K	M	N
40	80	67	20.5	31	12.2	0	0	3/4"	0	0

