

# EW600V

	PERFORMAMCE DATA	COOLING		HEATING	
	NUMBER OF ROWS	4 ROWS	6 ROWS	2 ROWS	
				HEATING BY CHILLER	HEATING SYSTEM
	CAPACITY IN Kbtu/h / kW	17.1 / 5	19.8 / 5.8	14.3	30.3
	SESIBLE CAPACITY IN Kbtu/h / kW	14.4	15.4		
	WATER FLOW IN GPM	3.4	4	2.9	3.1
	WATER PRESSURE DROP IN FT H <sup>2</sup> O	8.5	7.9	4.3	4.4
	NOISE LEVEL (dBA)	41.5			
	WEIGHT (kg)	37	38		
CONDITIONS	DRY / WET BULB TEMP.	80°F/67°F - 26.6°C/19.4°C		70°F - 21.1°C	
	WATER TEMP. INLET (°F / °C)	45 / 7		113 / 45	160 / 71
	WATER TEMP. OUTLET (°F / °C)	55 / 12.8		103 / 40	140 / 60
COIL	FACE AREA (ft <sup>2</sup> / m <sup>2</sup> )	1.5 / 0.14			
	LENGTH (MM)	500			
	AIR FLOW VELOCITY (fpm / m/sec)	400 / 2			
	HEADER DIAMETER (in)	7/8"			
BLOWER	AIR FLOW (CFM / m <sup>3</sup> / h)	600 / 1020			
	TYPE	DD 7x10			
	MOTOR POWER (HP / kW)	1/8		0.09	
	NO. OF SPEEDS	4			
	HIGH SPEED (RPM)	1400			
	POWER SUPPLY	230v/50Hz/1PH			
OPTIONAL	VALVE	ON/OFF / PROP			
	ELECTRIC HEATING (kW)	kW			
	OUTDOOR CONDITIONS	YES / NO			

Noise level at 1.5m distance from ducted (supply and return) unit

D	H	L	A	C	E	B	J	K	M	N
40	80	67	20.5	31	12.2	0	0	3/4"	0	0

