

EW800

	PERFORMAMCE DATA	COOLING		HEATING	
	NUMBER OF ROWS	4 ROWS	6 ROWS	2 ROWS	
				HEATING BY CHILLER	HEATING SYSTEM
	CAPACITY IN Kbtu/h / kW	22.2 / 6.5	28.8 / 8.4	18.5	39.9
	SESIBLE CAPACITY IN Kbtu/h / kW	17.3	22.4		
	WATER FLOW IN GPM	4.1	6	3.8	4.1
	WATER PRESSURE DROP IN FT H ₂ O	5.9	9.5	8	8.6
	NOISE LEVEL (dBA)	42			
	WEIGHT (kg)	44	46		
CONDITIONS	DRY / WET BULB TEMP.	80°F/67°F - 26.6°C/19.4°C		70°F - 21.1°C	
	WATER TEMP. INLET (°F / °C)	45 / 7		113 / 45	160 / 71
	WATER TEMP. OUTLET (°F / °C)	55 / 12.8		103 / 40	140 / 60
COIL	FACE AREA (ft ² / m ²)	1.91 / 0.18			
	LENGTH (MM)	500			
	AIR FLOW VELOCITY (fpm / m/sec)	420 / 2.1			
	HEADER DIAMETER (in)	1.1/8"			
BLOWER	AIR FLOW (CFM / m ³ / h)	800 / 1360			
	TYPE	DD 7x10			
	MOTOR POWER (HP / kW)	1/5		0.15	
	NO. OF SPEEDS	4			
	HIGH SPEED (RPM)	1400			
	POWER SUPPLY	230v/50Hz/1PH			
OPTIONAL	VALVE	ON/OFF / PROP			
	ELECTRIC HEATING (kW)	kW			
	OUTDOOR CONDITIONS	YES / NO			

Noise level at 1.5m distance from ducted (supply and return) unit

D	H	L	A	C	E	B	J	K	M	N
70	40	65	26.4	31	12.2	0	55	3/4"	35.4	99.5

