

# EW1500LFA

	PERFORMANCE DATA	COOLING		
	NUMBER OF ROWS	6 ROWS	6 ROWS	8 ROWS
	CAPACITY IN Kbtu/h	79.0	104.1	111.5
	SENSIBLE CAPACITY IN Kbtu/h	50.8	55.5	58.5
	WATER FLOW IN GPM	11.6	20.8	22.3
	WATER PRESSURE DROP IN FT H <sub>2</sub> O	9.5	7.8	8.2
	NOISE LEVEL (dBA)	46		
	WEIGHT (kg)	48	50	50
CONDITIONS	DRY / WET BULB TEMP.	95°F/79°F - 35°C/26.1°C		
	WATER TEMP. INLET (°F / °C)	45 / 7		
	WATER TEMP. OUTLET (°F / °C)	55 / 12.8		
COIL	FACE AREA (ft <sup>2</sup> / m <sup>2</sup> )	3.19 / 0.3		
	LENGTH (MM)	1060		
	AIR FLOW VELOCITY (fpm / m/sec)	470 / 2.4		
	HEADER DIAMETER (in)	1 1/8"		
BLOWER	AIR FLOW (CFM / m <sup>3</sup> / h)	1500 / 2550		
	TYPE	2X DD 7X10		
	MOTOR POWER (HP / kW)	2X 1/5		
	NO. OF SPEEDS	4		
	HIGH SPEED (RPM)	1400		
	POWER SUPPLY	230v/50Hz/1PH		
OPTIONAL	VALVE	ON/OFF / PROP		
	ELECTRIC HEATING (kW)	kW		
	OUTDOOR CONDITIONS	YES / NO		

Noise level at 1.5m distance from ducted (supply and return) unit

D	H	L	A	C	E	B	J	K	M	N
60	31	121.5	20.5	31	12.2	20	46.4	3/4"	26.2	118

