

# EW3000SQ

	PERFORMAMCE DATA	COOLING		HEATING	
NUMBER OF ROWS	4 ROWS	6 ROWS	2 ROWS		
			HEATING BY CHILLER	HEATING SYSTEM	
CAPACITY IN Kbtu/h / kW	91.9 / 27	120.4 / 35.3	76	163.9	
SESIBLE CAPACITY IN Kbtu/h / kW	70.6	85.5			
WATER FLOW IN GPM	18.4	24.1	15.5	16.8	
WATER PRESSURE DROP IN FT H <sub>2</sub> O	7	8.4	8.6	9.5	
NOISE LEVEL (dBA)	44.5				
WEIGHT (kg)	0	120			
CONDITIONS	DRY / WET BULB TEMP.	80°F/67°F - 26.6°C/19.4°C		70°F - 21.1°C	
	WATER TEMP. INLET (°F / °C)	45 / 7		113 / 45	160 / 71
	WATER TEMP. OUTLET (°F / °C)	55 / 12.8		103 / 40	140 / 60
COIL	FACE AREA (ft <sup>2</sup> / m <sup>2</sup> )	7.1 / 0.66			
	LENGTH (MM)	1180			
	AIR FLOW VELOCITY (fpm / m/sec)	493 / 2.5			
	HEADER DIAMETER (in)	0			
BLOWER	AIR FLOW (CFM / m <sup>3</sup> / h)	3000 / 5100			
	TYPE	2X DD 9X11			
	MOTOR POWER (HP / kW)	2X 1/2		2X 0.37	
	NO. OF SPEEDS	5			
	HIGH SPEED (RPM)	920			
	POWER SUPPLY	230v/50Hz/1PH			
OPTIONAL	VALVE	ON/OFF / PROP			
	ELECTRIC HEATING (kW)	kW			
	OUTDOOR CONDITIONS	YES / NO			

Noise level at 1.5m distance from ducted (supply and return) unit

D	H	L	A	C	E	B	J	K	M	N
70	63	139	44	36.3	26.5	29	55	7/8"	55.6	136

